

ShineNET

Growatt

V.1.2

2010-11-19

Software Version	Date	Notes
1.0	2010/6/22	New
1.1	2010/7/21	Add 4.4
1.2	2010/8/31	Add 5.3.3 and 6
1.2	2010/9/20	Add 5.3.4
1.2	2010/9/20	Add 4.5
1.2	1020/11/19	Update some pictures

Contents

1 Introduction.....	3
2 Specification.	3
3 Communication network application	4
4 Software	4
4.1 Installation.....	4
4.2 User registe	4
4.3 Interface	5
4.4 Language settings.....	7
4.5 About ShineNET	9
5 Software Operation	10
5.1 Connection settings	10
5.1.1 Connect inverter and disconnect	11
5.2 Parameter setting.....	12
5.3 Working information	13
5.3.1 Waveform diagram Interface.....	13
5.3.2 Multi-inverter monitoring interface	19
5.3.3 PV System Information Interface.....	21
5.3.4 PV System Information Interface Other.....	22
6 Q&A.....	23


1 Introduction

ShineNet is designed to collect data from Growatt Inverters with strong analysis functions. It has multi-communication channels and completed data analysis function. Users could monitor the status of Growatt inverters in real-time, browse and analysis the history data in the past.

2 Specification.

1. Multi-communication: RS232, Bluetooth
2. Acquiring data from multi-inverters.
3. Real time data detection, history data review and analysis.
4. Comparing multi-inverters data.
5. Multi-language
6. Operation system support for Windows XP/Vista/Win7/2000/2003 .

3 Communication network application



4 Software

4.1 Installation

ShineNet is developed in C# language. While the operation system is below Vista system, should install Freamwork2.0 in advance. Framwork2.0 could be installed by the "dotnetfx.exe" in the install package.

For operation system which already include framework2.0

4.2 User registe

While using the ShineNet first in the operation system, below dialogue will pop up.




Fig 4.2.1

Fill in your register name and password.

User could get some special function through our specify account and password.

4.3 Interface

ShineNET Interface could be divide into 4 region:

- System menu
- System button
- Inverter list
- PV System information



Fig 4.3.1

a). System Menu bar:

SoftSystem: software settings menu

System Set: access the communication setting dialogue.

Soft Language:

Exit: exist ShineNet

Inverter: Inverter operation menu

Connect/Disconnect: connect or disconnect the computer and inverter

Setting: access the inverter parameter settings.


Interface:


Change Interface: Switch the interface between Wave diagram and multi-inverters monitoring interface.

b) System Button:



: connect or disconnect inverter;

If disconnect the inverter, the button  will be lighted,

If the inverter are already connected,  will be lighted.



: access inverter parameter setting. If user does not specify a inverter, it will access the communication setting interface.



: access the communication setting interface;



: access the interface of multi-inverter monitoring interface;



: switch the interfaces;

c) Inverter List


This region is used to show the inverter series number and communication protocol.



indicate the list title and selected node;



: indicate the inverter is connected by RS232

: indicate the inverter is connected by Bluetooth

d) PV System information

This region is used to show the working information of inverters. It include two interfaces: Waveform diagram and multi-inverter monitoring interface.

Waveform Diagram Interface: provide power curves, data and fault information, all these information could change by time setting. Fig 3.3.1 for reference.

Multi-inverters Monitoring Interface: provide specified data and power curves of multi-inverters, it is easy for users to check and compare the situation of these inverters. Fig 3.3.2 for reference.



Fig4.3.2

4.4 Language settings

Access menu "SoftSystem->SoftLanguage->", choose your favorite language.



Fig4.4.1

Customize language:

- Open the document folder of the software, open the file "LanguageData.xml";
- Choose a language that you will not use, for example Chinese/简体中文.

The position is at the <MLanguages>

```
<LanguageList>.
  <LX> Language <LX>
  <?xml version="1.0" encoding="utf-8"?>
  <MLanguages>
    <LanguageList>
      <L0>English</L0>
      <L1>简体中文</L1>
      <L2>Français</L2>
      <L3>Deutsch</L3>
      <L4>Español</L4>
      <L5>Language Italiano</L5>
    </LanguageList>
  </MLanguages>
  <L0>
    <MainMenuTitle>
      <m0>SoftSystem</m0>
      <m00>System Set</m00>
      <m01>Soft Language</m01>
      <m02>Exit</m02>
      <m1>Inverter</m1>
```

Fig4.4.2

- Translate the language in the position<MLanguages>

<LanguageList>.

<LX> Language <LX>

Users can copy English version to replace the useless language, then translate the copied english words directly. Please check fig. 4.4.2 as reference.




Fig4.4.3




Fig4.4.4





Fig4.4.5

d) save the modified the file and reboot the software.


4.5 About ShineNET

Access menu "Help->About ShineNET" go to "About ShineNET" interface, you can get the software version and the user manual document, also you can get the newest information of Growatt.



5 Software Operation

5.1 Connection settings

Click  or access "SoftSystem->System Set", will get the communication settings interface.




Fig 5.1.1

SystemSetting:

DataPath: The save path for inverter data;

DelayTime: The communication interval, the value should be over 2 second.

SerialPort:

SerialPort: enable RS232 function;

COMPort: the port of PC RS232;

Bluetooth:

Bluetooth: enable Bluetooth function;

BluetoothList: local bluetooth devices list, click the item to choose;

BluetoothAddr: the address of the communication bluetooth;

DeviceName、DeviceName2: the bluetooth device Name of inverter, to filter outlying bluetooth device. If users can not connect to a new inverter, you can set one of the DeviceName2 to empty, the software will connect all exist bluetooth devices;

SerchFast: it will search the bluetooth device already in the memory. While new device added or could not find the old device, user could cancel the function.

Internet:

Reserve function;

5.1.1 Connect inverter and disconnect








Connect inverter: Click  or access "Inverter->Connect/Disconnect" to connect inverter. While the connection set up, the symbol  will change to . PC will connect the inverter through specify communication mode. The software will list the inverter serial number and communication mode.



Fig 5.1.2

Disconnect: Click  or access "Inverter->Connect/Disconnect" to disconnect. The symbol  will be change to  .

5.2 Parameter setting

a). Choose inverter, then click the inverter name of "Inverterlist", the communication mode will be  , it indicate the communication is started.

b). Click  or access " Inverter-> Setting" to inverter parameter settings interface.

Notice: normal user can only modify the Items in the "UserSet" ;




Fig 5.2.1

LCD Contrast: set inverter LCD contrast;

d). The software will pop up "SetResult" dialogue show the result.

The main working information will be show in the "Inverter wave&data" region. The region can show two interface, "waveform diagram" and "multi-inverter monitoring interface". Fig 3.3.1 and Fig 3.3.2 for reference.

Waveform interface is main interface. It is used to inquiry data, power curves and fault information online or in history.

Waveform diagram Interface has been divided to operation region, parameter region and waveform region;




Fig 5.3.1

Operation region: include operation options, inverter list, waveform option, date and inquiry button.

Parameter region: indicate the default parameter of working inverters.

Waveform region: show the waveform or data of the inquiry result.

5.3.1.1 Inquiry power curves

Follow the steps in the operation region: RealTimeWave->SerialNo.-> -> ->Search, users will have the a day waveform of the specify inverter. The software will automatically update the curves after the operation.




Fig 5.3.2

5.3.1.2 Inquiry real time data

Follow the steps in the operation region: RealTimeData->SerialNo.-> -> ->Search, users will have the a day data of the specify inverter. The software will automatically update the datasheet after the operation.



Fig 5.3.3

5.3.1.3 Inquiry history waveform

History waveform include:

TimelyDay: power curve diagram of specify date

DaylyinMonth: column diagram for every day electric energy production in one specify month.

MonthlyInYear: column diagram for every month electric energy production in one specify year.

YearlyInLifetime: column diagram for every year electric energy production.

Follow the steps in the operation region:

HistoryWave->SerialNo.->WaveType->Date->Search, users will have the waveform of the specify inverter.




Fig 5.3.4




Fig 5.3.5





Fig 5.3.6

5.3.1.4 Inquiry history data

Follow the steps in the operation region: HistoryData->SerialNo.-> ->Date->Serch, users will have the datasheet of the specify inverter in the specify date.

GROWATT NEW ENERGY CO., LTD
Yongchang Building, Xicheng Industrial
Zone, Bao'an District, Shenzhen, China

浙江格瑞特新能源有限公司
深圳宝安区西乡街道西成工业区永昌楼
P.C. 518000

T / F + 86 755 2749 1460
info@ginverter.net
www.ginverter.com

Id	TimeNow	Status	Vpv1	Vpv2	Ppv	Vac	Iac	Fac	Pac
7263	23:59:59	1	3.5	282.5	3506.4	236.3	14.5	49.94	3436.3
7262	23:59:57	1	3.5	283.1	3565.5	236.3	14.7	49.96	3494.2
7261	23:59:55	1	3.5	283.1	3578.8	235.3	14.9	49.96	3507.3
7260	23:59:43	1	2.9	283.1	3563.8	236.3	14.7	49.96	3492.6
7259	23:59:41	1	2.9	283.1	3595.3	236.3	14.9	49.96	3523.4
7258	23:59:39	1	3.5	282.5	3583.6	237.3	14.7	49.96	3512
7257	23:59:33	1	3.5	283.1	3575.5	236.3	14.8	49.95	3504
7256	23:59:31	1	2.9	281.9	3561.5	236.3	14.7	49.95	3490.3
7255	23:59:29	1	3.5	283.1	3569.1	236.3	14.8	49.93	3497.8
7254	23:59:17	1	3.5	282.5	3578.9	236.3	14.8	49.95	3507.4
7253	23:59:15	1	3.5	282.5	3582	236.3	14.8	49.96	3510.4
7252	23:59:13	1	3.5	283.1	3588.1	235.3	14.9	49.96	3516.4
7251	23:59:07	1	3.5	282.5	3567.8	236.3	14.7	49.97	3496.5
7250	23:59:05	1	2.9	282.5	3569.7	235.3	14.8	49.95	3498.4
7249	23:59:03	1	2.9	283.1	3569.8	235.3	14.8	49.97	3498.5
7248	23:58:50	1	3.5	282.5	3560.6	235.3	14.8	49.94	3489.4
7247	23:58:48	1	3.5	283.1	3567.5	234.4	14.9	49.96	3496.2
7246	23:58:46	1	2.9	282.5	3590	236.3	14.8	49.97	3518.2
7245	23:58:40	1	2.9	282.5	3526.4	236.3	14.6	49.98	3455.9
7244	23:58:38	1	2.9	283.1	3561.7	236.3	14.7	49.98	3490.5
7243	23:58:36	1	3.5	282.5	3588	236.3	14.8	49.98	3516.3
7242	23:58:24	1	2.9	282.5	3587	236.3	14.8	49.99	3515.3

Fig 5.3.7

5.3.1.5 Inquire fault information

Follow the steps in the operation region: ErrorData->SerialNo.-> ->Date->Search, users will have the fault sheet of the specify inverter in the specify month.

Id	FaultTime	SerialNo	FaultType	FaultValue
2	2010/11/4 15:2...	5KB0300000	No AC Connect...	0
1	2010/11/4 13:4...	5KB0300000	No AC Connect...	0

Fig 5.3.8

5.3.2 Multi-inverter monitoring interface

Multi-inverter monitoring in one screen, it is easy to check many inverter working situation.



Fig 5.3.9

5.3.2.1 monitoring interface

Click  or access "Interface->Interface Set" to inverter choosing dialogue.




Fig 5.3.10

SelecteInverter: the page of selecting inverters;

SelecteData: the page of select inverter parameters;

Add: add new inverters;

a). choose inverters

Choose "SelecteInverter" page, click the inverter on the left inverter list. Click



button, the screen will show the inverter. Maximum number is 20.

b). Choose the inverter parameters.





Fig 5.3.11

Choose the "SelectData" page in the operation interface, then choose the parameters in the left list, click  button, the screen will show the chosen parameters. The maximum number is 4.

5.3.3 PV System Information Interface

In this interface you could see the total Power, Energy of your system, and also there are the load information for each inverter.




Fig 5.3.12

“xxW” is the Inverter power now;


“xx%” is the load percents;

Red means then inverter is in the fault status;

Green shows the load percents also;

5.3.4 PV System Information Interface Other

This interface has the same function as the interface in 5.3.3, but this is more intuitive.



6 Q&A

Q: Why cannot I find my inverter by RS232 or RS485 ?

A: First: Check do you have enable the communicate by Serial Port in 5.1 contact;
Second: Check your RS232 wire is The connected directly;
Third: Check the connection of RS485, make sure the Pin1 to Pin1 and Pin2 to Pin2;

Q: How do I connect my inverter to PC by RS485 ?

A: First: Connect the inverters to one string by RS485, make sure the Pin1 to Pin1 and Pin2 to Pin2;
Second: Connect one inverter to PC by RS485;
Third: Set the ShineNET communicate by Serial Port;

Q: Why cannot I find my inverter by Bluetooth ?

A: First : If the BTDevice is the first time used on this PC, should cancel the fast serch function in 5.1 connect Setting, try start connect for times, if could not find device also, you could set "Device Nmae2" to be empty, retry again.
Second: If there are more than one Bluetooth devices, and there is no result after you try the first operation, maybe this is caused by your BTRadio functions. Now you can get "USB Bluetooth Dongle" form Growatt, it can connect max 7 BTDevices at the same time.
Note: BTRadio: the Bluetooth radio on PC;
BTDevice: the Bluetooth device on Inverter;

Q: Why cannot I find the history data of my inverter ?

A: First: Check the Data path is right in 5.1 connect setting;
Second : Check the Data files are there under the data path, always is under "Datapath\Inverterdata\SerialNo\xxxxx.mdb";